



## **TOP SECRET COATINGS**

P. O. Box 3007, Arlington WA. 98223  
360-651-9050 FAX 360-548-8573  
info@topsecretcoatings.com  
www.topsecretcoatings.com

---

### **TS-204**

## **Sandable Latex Primer**

### **Sandable Latex Primer**

Sandable Latex Primer (TS-204) is the right choice when you want to achieve a glass-like finish indoors or outdoors. It's a high hiding, high build enhanced acrylic latex primer formulated to provide a sound base for paint that sands easily without gumming up sandpaper. It provides excellent adhesion and holdout. Your finish coat will last longer and cover better when using this premium grade primer.

Sandable Latex Primer features excellent adhesion to chalky surfaces and hard smooth materials. It provides a uniformly sealed surface designed to maximize paint performance while providing superior sandability over a wide variety of substrates. Creates a high film build up making it the perfect choice to seal and sand most any surface to a smooth finish.

Use it to establish a sealed uniform surface for the application of flat, satin, semi-gloss or gloss finishes. Exterior: Intended for use on new and previously painted surfaces including wood siding, shakes, trim, concrete, brick, stucco, cement composite siding, and clean metal surfaces. Interior: Intended for use on new and previously painted surfaces including furniture, trim, cabinets, walls, woodwork, ceilings, plaster, drywall, and masonry surfaces.

Coverage is approximately 200-300 square feet. Dry to the touch in one hour, sandable in just 2-4 hours. May require two or more coats. Coverage is approximately 300-350 square feet per gallon. Easy application, brush, roll or spray it on. Cleans up with water.

#### **Product Features**

- Sands to an ultra smooth finish.
- Fast dry formula is sandable in 2-4 hours.
- Provides high build.
- High adhesion.
- Breathing formula prevents blistering.
- Withstands extremes in weather.

# PRODUCT DATA

## TS-204 Sandable Latex Primer

**COLORS):** White

**PRODUCT TYPE:** Pigmented Acrylic Primer.

**DESCRIPTION:** A pigmented acrylic latex emulsion base wall primer-sealer specially formulated to provide excellent sandability while providing a sound base for paint. Its breathing-type formula lets moisture escape without the surface peeling, blistering, or cracking.

**Intended Use:** A sandable primer-sealer for interior or exterior surfaces including furniture, wallboard, ceramic tile, hardboard, plastic laminate, metal surfaces.

### PHYSICAL CHARACTERISTICS

**VISCOSITY:** 85+/- 3 KU's

**DRY TO TOUCH:** 30-45 minutes

**WEIGHT SOLIDS:** 51-53%

**TACK FREE:** 1 hour

**VOLUME SOLIDS:** 40-42%

**TIME TO TOP COAT:** 2 hours

**WEIGHT PER GALLON:** 11.67 lbs. per gal.

**DRY HARD:** 2 hours

**V.O.C.:** 144 grams per liter

**COLOR RANGE:** White (may be tinted)

**FLASH POINT:** N/A

**PRACTICAL COVERAGE:** 300-400 square feet per gallon depending on the porosity of the surface .

**SURFACE PREPARATION:** Surface must be dry, clean and free of all foreign agents and properly prepared.

**APPLICATION :** Apply by brush, roller or airless spray, making certain that the surface is well sealed. Usually only one coat is required to provide adequate sealing. Allow to dry, then recoat with the desired top coat