



TOP SECRET COATINGS

P. O. Box 3007, Arlington WA. 98223
360-651-9050 FAX 360-548-8573
info@topsecretcoatings.com
www.topsecretcoatings.com

TS-307 Multi-Purpose Oil Based Primer

Multi-Purpose Oil-Based Primer

Multi-Purpose Oil-Based Primer is versatile, easy to use and provides a sound base for a wide variety of top coating systems. It's a better way to begin when tannin bleeding, stains, water intrusion, mold and mildew are a concern. Our oil-alkyd formulation provides superior penetration over wood, drywall and other porous surfaces. It provides exceptional hide characteristics and resists mildew growth for extra protection in the most difficult circumstances and inclement climates.

Your finish coat will last longer and cover better when using Multi-Purpose Oil-Based Primer. It has exceptional hide characteristics and contains extra mildew-cide for wet climates. It is successful in sealing out moisture and Tannic-acid bleeds (Cedar bleed). It is sandable with excellent tooth and penetration. When sanded it will provide a glass-like smooth surface.

Use it to establish a sealed uniform surface for the application of flat, satin, semi-gloss or gloss finishes. Recommended for use on bare and previously painted surfaces where peeling, cracking, blistering and chalking have been a problem previously.

Intended for use on exterior and interior walls, woodwork, ceilings, plaster, drywall, brick, wood siding, aluminum siding, galvanized metal and gutters. It is acceptable for use with either oil based or waterborne paints. Coverage is approximately 300-400 square feet per gallon. May be brushed, rolled or sprayed.

Product Features

- Prevents peeling paint on new construction.
- Good tannin blocking properties.
- Penetrates and seals porous substrates.
- Highly versatile, use it almost anywhere.
- High adhesion with excellent build.
- Sandable formula.
- Withstands extremes in weather.
- Prevents water intrusion.

PRODUCT DATA

TS-307 Multi-Purpose Oil-Based Primer

COLOR(S): White (may be tinted).

PRODUCT TYPE: Alkyd Oil Primer.

DESCRIPTION: A top quality oil alkyd primer designed to prime and seal new wood surfaces and weathered painted surfaces. Acceptable for use in exterior and interior applications. It is a controlled penetrating primer may be used in a wide variety of applications. It is an ideal foundation for oil and latex finish coats.

Intended Use: All exterior and interior surfaces.

PHYSICAL CHARACTERISTICS

VISCOSITY: 80 +/-3 KU's

DRY TO TOUCH: 6-8 hours

WEIGHT SOLIDS: 82-86%

TACK FREE: 8 hours

VOLUME SOLIDS: 68-70%

TIME TO RECOAT: Overnight

WEIGHT PER GALLON: 13.72 lbs. per gal.

DRY HARD: 18 hours

V.O.C.: 435 grams per liter

COLOR RANGE: White (may be tinted)

FLASH POINT: 105° F.

PRACTICAL COVERAGE: 300-500 square feet per gallon depending on the type of surface to be coated.

SURFACE PREPARATION: Surface must be dry, clean and free of all foreign agents and properly prepared.

APPLICATION: Brush, roller or airless spray.

THINNING: Thin if necessary with TS-101 Thinner.

CLEAN-UP: Tools and equipment may be cleaned with TS-101 Thinner.