



TOP SECRET COATINGS

P. O. Box 3007, Arlington WA. 98223
360-651-9050 FAX 360-548-8573
info@topsecretcoatings.com
www.topsecretcoatings.com

TS-500 PVA Primer

Provide A Sound Base For Paint

PVA Primer provides a sound base for a wide variety of top coating systems. Finish coats will last longer and paint will cover better when PVA Primer is used. It is a professional primer sealer for new construction and all unpainted interior drywall and texture coatings.

A proprietary formula that includes acetate instead of the usual acrylic which is an improvement for sealing out moisture and odors. Designed for the professional painter and for the quality conscious consumer. Formulated for excellent adhesion, even sealing and holdout, it provides a uniform foundation for alkyd or latex paint. Use it to establish a sealed uniform surface for the application of flat, satin, semi-gloss or gloss finishes. Recommended for use on bare and previously painted surfaces.

PVA Primer is excellent for flat, satin, semi-gloss and gloss top coats. Specially formulated for use with Top Secret interior and exterior paints. Use on walls, ceilings, plaster, drywall, stucco and brick. Use to establish a sealed uniform surface for the application of flat, satin, semi-gloss or gloss finishes. Covers up to 350 square feet per gallon. Washes up with water. Apply using a brush, roller or spray. Thins and washes up easily with water.

Product Features

- Prevents peeling paint on new construction.
- Acetate out performs acrylic.
- Provides a sound base for paint.
- Good stain blocking properties.
- Penetrates and seals porous substrates.
- Highly versatile, use it almost anywhere.
- High adhesion with good build.

PRODUCT DATA

TS-500 PVA Primer

COLOR(S): White (may be tinted).

PRODUCT TYPE: Flat Pigmented PVA Emulsion.

DESCRIPTION: A pigmented latex emulsion base wall sealer specially formulated for interior wallboard surfaces.

Intended Use: For sealing interior wallboard surfaces, interior cement block, plaster or brick surfaces.

PHYSICAL CHARACTERISTICS

VISCOSITY: 90 k.u.

DRY TO TOUCH: 30 minutes

WEIGHT SOLIDS: 44-47%

TACK FREE: 30 minutes-1hour

VOLUME SOLIDS: 29-32%

TIME TO RECOAT: 1-3 hours

WEIGHT PER GALLON: 10.53 lbs. per gal.

DRY HARD: 2 hours

V.O.C.: 27 grams per liter

COLOR RANGE: White, tints

FLASH POINT: N/A

PACKAGING: 1 or 5 gallon

PRACTICAL COVERAGE: 300-500 square feet per gallon depending on the porosity of the surface to be coated.

SURFACEPREPARATION: Surface must be dry, clean and free of all foreign agents and properly prepared.

APPLICATION: Apply by brush, roller or airless spray, making certain that the surface is well sealed. Usually only one coat is required to provide adequate sealing. Allow to dry, then recoat with the desired interior paints.

THINNING: Thinning is not recommended.

CLEAN-UP: Tools and equipment may be cleaned with normal tap water.